

Telefax: + 49 (0) 7351 56 1488

according to Regulation (EC) No 1907/2006

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

KaVo QUATTROcare plus Spray

Product code:

1.011.4624 1.011.5720

Further trade names

QUATTROcare plus Spray 2140, QUATTROcare plus Spray 2140P

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name: Kaltenbach & Voigt GmbH

Street: Bismarckring 39
Place: D-88400 Biberach
Telephone: +49 (0) 7351 56 0

e-mail: sdb@kavo.com

e-mail (Contact person): support@gefahrstoff.com Internet: http://www.kavo.com/

1.4. Emergency telephone +49 (0) 7351 56 4000 (24 h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Revision No: 3,1 - Replaces version: 3

IRL - EN



according to Regulation (EC) No 1907/2006

Page 2 of 11

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification according to	o Regulation (EC) No. 1272/2008 [0	CLP]			
106-97-8	butane					
	203-448-7	601-004-00-0	01-2119474691-32			
	Flam. Gas 1, Liquefied gas; H220 H280					
75-28-5	isobutane			35 - < 40 %		
	200-857-2	601-004-00-0				
	Flam. Gas 1, Liquefied ga					
8042-47-5	White mineral oil (petrole	15 - < 20 %				
	232-455-8		01-2119487078-27			
	Asp. Tox. 1; H304					
74-98-6	propane					
	200-827-9	601-003-00-5	01-2119486944-21			
	Flam. Gas 1, Liquefied gas; H220 H280					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

Wash with plenty of water.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.



according to Regulation (EC) No 1907/2006

Page 3 of 11

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Extremely flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Vapours can form explosive mixtures with air.

Further information on handling

Avoid contact with skin, eyes and clothes.



according to Regulation (EC) No 1907/2006

Page 4 of 11

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Protect against direct sunlight. Protect against: Frost.

7.3. Specific end use(s)

The product is intended for professional use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
106-97-8	Aliphatic hydrocarbon gases, Alkanes (C1-C4), Butane	1000	-		TWA (8 h)	
		-	-		STEL (15 min)	
74-98-6	Aliphatic hydrocarbon gases, Alkanes (C1-C4), Propane	1000	-		TWA (8 h)	
		-	-		STEL (15 min)	

8.2. Exposure controls

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

No special measures are necessary.

Respiratory protection

No special measures are necessary.

Environmental exposure controls

Avoid release to the environment.



according to Regulation (EC) No 1907/2006

Page 5 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid (Aerosol)
Colour: light yellow
Odour: characteristic

Test method

pH-Value: not determined DIN 19268

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

-40 °C

Flash point:

-80 °C

Flammability

Solid: not applicable
Gas: not applicable

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits: 1 vol. %
Upper explosion limits: 11 vol. %
Ignition temperature: not determined

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,853 g/cm³ DIN 51757

Water solubility: practically insoluble

Solubility in other solvents

not determined

Partition coefficient:

Viscosity / dynamic:

not determined

viscosity / kinematic:

15,5 mm²/s

Vapour density:

not determined

evaporation rate:

not determined

9.2. Other information

Odour threshold: not determined



according to Regulation (EC) No 1907/2006

Page 6 of 11

Density: Data apply to the technically active substance.

pressure: - bar (20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Do not expose to temperatures above 50 °C.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
8042-47-5	White mineral oil (petrole	White mineral oil (petroleum)					
	oral	LD50 mg/kg	> 5000	Rat	Manufacturer		
	dermal	LD50 mg/kg	> 2000	Rabbit	Manufacturer		
	inhalative (4 h) aerosol	LC50 mg/l	> 5000	Rat	Manufacturer		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Page 7 of 11

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
8042-47-5	White mineral oil (petroleum)						
	Acute fish toxicity	LC50 mg/l	> 100		Brachydanio rerio (zebra-fish)	Manufacturer	
	Acute algae toxicity	ErC50 mg/l	> 100	1	Desmodesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50 mg/l	> 100		Daphnia magna (Big water flea)	Manufacturer	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
75-28-5	isobutane	2,8
8042-47-5	White mineral oil (petroleum)	> 3,5
74-98-6	propane	2,36

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations



according to Regulation (EC) No 1907/2006

Page 8 of 11

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



according to Regulation (EC) No 1907/2006

Page 9 of 11



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no.

14.6. Special precautions for user

Warning: Flammable gases.



according to Regulation (EC) No 1907/2006

Page 10 of 11

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3: White mineral oil (petroleum) Entry 40: butane; isobutane; propane

2010/75/EU (VOC): No information available.

Information according to 2012/18/EU

(SEVESO III):

P3a FLAMMABLE AEROSOLS

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.



according to Regulation (EC) No 1907/2006

Page 11 of 11

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.